

THRESHOLDS

1/2" (12.7mm) Rise Thresholds

1/2" (12.7mm)

4" (102mm)

DS400A Extruded aluminum mill finish
DS400D Bronze anodized

1-1/2 HR
Intertek **RATING**

.518 lbs./ft. (.771 kg/m)

1/2" (12.7mm)

5" (127mm)

DS95A Extruded aluminum mill finish

1-1/2 HR
Intertek **RATING**

.493 lbs./ft. (.734 kg/m)

1/2" (12.7mm)

5" (127mm)

DS500A Extruded aluminum mill finish
DS500D Bronze anodized

1-1/2 HR
Intertek **RATING**

.606 lbs./ft. (.902 kg/m)

1/2" (12.7mm)

5" (127mm)

DS505A Extruded aluminum mill finish

1-1/2 HR
Intertek **RATING**

.602 lbs./ft. (.877 kg/m)

1/2" (12.7mm)

6" (152mm)

DS600A Extruded aluminum mill finish
DS600D Bronze anodized

1-1/2 HR
Intertek **RATING**

.747 lbs./ft. (1.112 kg/m)

1/2" (12.7mm)

7" (178mm)

DS700A Extruded aluminum mill finish
DS700D Bronze anodized

1-1/2 HR
Intertek **RATING**

.913 lbs./ft. (1.359 kg/m)

1/2" (12.7mm)

8" (203mm)
product not shown full width

DS800A Extruded aluminum mill finish
DS800D Bronze anodized

1-1/2 HR
Intertek **RATING**

1.158 lbs./ft. (1.724 kg/m)

Thresholds on this page are supplied with punched countersunk holes with screws and plugs and are only available in the following NET lengths (except as noted):

36-1/2"	927mm
49"	1245mm
73"	1854mm
110"	2794mm
147"	3734mm