

THRESHOLDS

1/4" (6.4mm) Low Rise Thresholds

Thresholds on this page are supplied with punched countersunk holes with screws and plugs and are only available in the following NET lengths (except as noted):

| | |
|---------|--------|
| 36-1/2" | 927mm |
| 49" | 1245mm |
| 73" | 1854mm |
| 110" | 2794mm |
| 147" | 3734mm |

DS4000A Extruded aluminum mill finish
DS4000D Bronze anodized

1-1/2 HR RATING
 Intertek
 .598 lbs./ft. (.890 kg/m)

DS5000A Extruded aluminum mill finish
DS5000D Bronze anodized

1-1/2 HR RATING
 Intertek
 .712 lbs./ft. (1.06 kg/m)

DS6000A Extruded aluminum mill finish
DS6000D Bronze anodized

1-1/2 HR RATING
 Intertek
 .835 lbs./ft. (1.243 kg/m)

DS7000A Extruded aluminum mill finish
DS7000D Bronze anodized

1-1/2 HR RATING
 Intertek
 .954 lbs./ft. (1.42 kg/m)

DS8000A Extruded aluminum mill finish
DS8000D Bronze anodized

product not shown full width

1-1/2 HR RATING
 Intertek
 1.1047 lbs./ft. (1.638 kg/m)