

# THRESHOLDS

## Specialty Thresholds

3/16" (4.7mm)  
 2-1/4" (57mm)  
**DS2000A** Extruded aluminum mill finish  
**DS2000D** Bronze anodized

**1-1/2 HR**  
**Intertek RATING**  
 .259 lbs./ft. (.386 kg/m)

1/8" (3mm)  
 4" (102mm)  
**DS4000AL** Extruded aluminum mill finish. Holes are punched & staggered when specified. Length available: 12ft (3658mm) only.

**1-1/2 HR**  
**Intertek RATING**  
 .346 lbs./ft. (.515 kg/m)

Thresholds on this page are supplied with punched countersunk holes with screws and plugs and are only available in the following NET lengths (except as noted):

36-1/2"	927mm
49"	1245mm
73"	1854mm
110"	2794mm
147"	3734mm

## Stainless Steel

1/2" (12.7mm)  
 5" (127mm)  
**DS510SS** Stainless steel, 304 SS brushed finish. Lengths available: 36-1/2" (927mm) 73" (1854mm) 120" (3048mm).

**1-1/2 HR**  
**Intertek RATING**

## Heavy Duty (H) Thresholds (Mill finish is standard. Bronze anodized available on custom order)

1/2" (12.7mm)  
 5" (127mm)  
**DS500HA** Extruded aluminum heavy duty, mill finish

**1-1/2 HR**  
**Intertek RATING**  
 1.060 lbs./ft. (1.578 kg/m)

1/2" (12.7mm)  
 6" (152mm)  
**DS600HA** Extruded aluminum heavy duty, mill finish

**1-1/2 HR**  
**Intertek RATING**  
 1.312 lbs./ft. (1.952 kg/m)

1/2" (12.7mm)  
 7" (178mm)  
**DS700HA** Extruded aluminum heavy duty, mill finish

**1-1/2 HR**  
**Intertek RATING**  
 1.38 lbs./ft. (2.054 kg/m)

1/2" (12.7mm)  
 8" (203mm) product not shown full width  
**DS800HA** Extruded aluminum heavy duty, mill finish

**1-1/2 HR**  
**Intertek RATING**  
 1.662 lbs./ft. (2.473 kg/m)