



ADHESIVE-BACKED JAMB SEALS


Vinyl-Flex (Compression) Seal, Adhesive-Backed




DS117T84 tan, 84" (2134mm) only
DS117W84 white




DS116T84 tan, 84" (2134mm) only
DS116W84 white



Compression Seal, Adhesive-Backed




DS415B96 brown, 96" (2438mm)
DS415B144 brown, 144" (3658mm)
DS415W96 white, 96" (2438mm)
DS415W144 white, 144" (3658mm)
DS415BL144 black, 144" (3658mm)



Intumescent Seal, Adhesive-Backed (Custom order, call for manufacturing time)

1/8" (3.2mm) clearance required between doors & between door & frame. Intumescent materials are formulated to expand at 375° to 400° Fahrenheit (190° to 404° Celsius) up to 8-10 times their original thickness; completely sealing the gap (jamb & head) & between doors during a fire.



DS200-17BL black, 17ft roll (5.18m)
DS200-21BL black, 21ft roll (6.40m)

Application:



20, 45, 60, 90 Minute rated category B wood doors up to:
 Single swing: 4'0 x 9'0 / Pairs: 8'0 x 9'0



Meeting Edge Application up to 8'0 x 9'0 pairs of category B wood doors: 20 Minute rated with single strip installed



45, 60 Minute rated with two strips installed

All adhesive gaskets have a limited shelf life. These products must be used within 6 months of purchase & must be stored between 50° & 100° Fahrenheit (10° & 38° Celsius).