

THRESHOLDS

1/4" (6.4mm) Low Rise Thresholds

Thresholds on this page are supplied with punched countersunk holes with screws and plugs and are only available in the following NET lengths (except as noted):

36-1/2"	927mm
49"	1245mm
73"	1854mm
110"	2794mm
147"	3734mm

1/4" (6.4mm)

4" (102mm)

DS4000A Extruded aluminum mill finish
DS4000D Bronze anodized

1-1/2 HR
Intertek RATING
 .598 lbs./ft. (.890 kg/m)

1/4" (6.4mm)

5" (127mm)

DS5000A Extruded aluminum mill finish
DS5000D Bronze anodized

1-1/2 HR
Intertek RATING
 .712 lbs./ft. (1.06 kg/m)

1/4" (6.4mm)

5" (127mm)

DS5005C Extruded aluminum clear anodized
DS5005D Bronze anodized

1-1/2 HR
Intertek RATING
 .730 lbs./ft. (1.064 kg/m)

1/4" (6.4mm)

6" (152mm)

DS6000A Extruded aluminum mill finish
DS6000D Bronze anodized

1-1/2 HR
Intertek RATING
 .835 lbs./ft. (1.243 kg/m)

1/4" (6.4mm) **DS7005C SPECIAL ORDER ONLY, MINIMUM RUN APPLIES**

7" (178mm)

DS7005C Extruded aluminum clear anodized only.
 Special order only, minimum run applies.

1-1/2 HR
Intertek RATING
 1.417 lbs./ft. (2.108 kg/m)

1/4" (6.4mm)

7" (178mm)

DS7000A Extruded aluminum mill finish
DS7000D Bronze anodized

1-1/2 HR
Intertek RATING
 .954 lbs./ft. (1.42 kg/m)

1/4" (6.4mm)

8" (203mm)
 product not shown full width

DS8000A Extruded aluminum mill finish
DS8000D Bronze anodized

1-1/2 HR
Intertek RATING
 1.1047 lbs./ft. (1.638 kg/m)